

					
MEDITE, Redmondstown, Clonmel, Co. Tipperary, Ireland					
DOP09REV2 MEDITE TRICOYA EXTREME MDF.H-2					
EN 13986:2004					
Not Applicable					
04					
E1					
MDF.H-2					
External use as non-structural components					
<b>Thickness Range mm</b>	6 to <9	9 to <12	12 to <15	15 to <18	18
<b>Internal bond (N/mm<sup>2</sup>)</b>	0.80	0.80	0.80	0.80	0.80
<b>Swelling in thickness %</b>	2.5	2.0	2.0	1.5	1.5
<b>Internal bond after boil test (N/mm<sup>2</sup>)</b>	0.65	0.65	0.65	0.65	0.65
<b>Reaction to fire</b>	NPD	D-s2,d0	D-s2,d0	D-s2,d0	D-s2,d0
<b>Release of formaldehyde</b>	E1	E1	E1	E1	E1
<b>Release (content) of pentachlorophenol (PCP)</b>	≤5ppm	≤5ppm	≤5ppm	≤5ppm	≤5ppm
<b>Thermal resistance R Value m<sup>2</sup>k / W</b>	0.056	0.085	0.114	0.150	0.180
<b>Biological</b>	Use Classes 1,2,3, 4				

CE symbol

Name and address of manufacturer  
DoP reference.

Reference to harmonised standard

Notified body number

Year in which the CE mark was first affixed

Formaldehyde classification

Product technical class

Intended use

Thickness range

Declared performance